

Key Selling Points

1. Real time and automatic data upload to LogTag[®] Online so you can check the status and generate reports remotely.
2. Know the location and condition of your shipment while in transit with location, humidity, shock, light, and temperature sensors.
3. No need to rely on logistics staff to turn on flight mode, Auto Flight mode turns on automatically for you.
4. Made for air travel with a NiMH battery.



| Model | LogTag [®] LT5GEO | DeltaTrak FlashLink [®] Air 22493-01 | Sensitech TempTale Geo X | Controlant Saga |
|-------------------------------|---------------------------------------|---|---------------------------------------|--------------------------------------|
| Key Features | | | | |
| Temperature Measurement Range | -30 °C to +70 °C -22 °F to +158 °F | -30 °C to +70 °C -22 °F to +158 °F | -10 °C to +55 °C +14 °F to +131 °F | -20 °C to +50 °C -4 °F to +122 °F |
| Humidity Measurement Range | 0 %RH to 100 %RH non-condensing | 5 %RH to 95 %RH | 10 %RH to 90 %RH non-condensing | |
| Auto Flight Mode | | | | |
| Start Delay | 1 minute to 72 hours | N/A | 0 minutes to 24 hours | N/A |
| Shock Sensor | | | | |
| Cellular Connectivity | 4G/5G (with 2G fall-back) | 4G/5G (with 2G fall-back) | 4G/5G (with 2G fall-back) | 2G, 3G, and 4G (LTE) |
| Sampling Interval | 10 minutes | 5 minutes | 5 minutes to 2 hours | 10 minutes |
| Data Upload Interval | 1 hour - 24 hours | 15 minutes | 15 minutes | 1 hour - 12 hours |
| Maximum Battery Life | 90 days | 15 days | 60 days | 110 days |

Trust LogTag[®]



Every single logger goes through temperature cycling and testing, guaranteeing the reliability of our products.

Rest assured you have reliable and accurate loggers every time you use a LogTag[®] logger.