

TEMPERATURE INDICATOR WITH DISPLAY



LogTag®

TIC20
Temperature Indicator
with 40 Day Display



The LogTag® TIC20 is a disposable electronic temperature indicator for use in monitoring temperature & time statistics in pharmaceutical transport applications of up to 40 days duration.

The LogTag® TIC20 is factory pre-configured with one of two monitoring profiles to meet the WHO PQS parameters.

WHO PQS Pre-qualified:



WHO Type A/B



WHO Type C

Features



Records temperature from -30°C to +60°C.



Clear indication of temperature history/alarm status at all times.



Meets the WHO PQS performance specification E06/TR07.2.



Review button to display daily statistics in sequence.



Up to 40 days temperature records can be viewed on the display.

Applications



Pharmaceuticals Transportation



Vaccine Transportation



Transportation



Air Transportation

Specifications

Product Model	TIC20
Sensor Measurement Range	-30°C to +60°C (-22°F to +140°F).
Operating Temperature Range	-30°C to +60°C (-22°F to +140°F).
Storage Temperature Range	-30°C to +65°C (-22°F to +149°F).
Rated Temperature Reading Accuracy	Better than $\pm 0.5^{\circ}\text{C}$ for -10°C to $+40^{\circ}\text{C}$ ($+14^{\circ}\text{F}$ to $+104^{\circ}\text{F}$). Better than $\pm 1.0^{\circ}\text{C}$ for -30°C to -10°C (-22°F to $+140^{\circ}\text{F}$). Better than $\pm 1.0^{\circ}\text{C}$ for $+40^{\circ}\text{C}$ to $+60^{\circ}\text{C}$ ($+104^{\circ}\text{F}$ to $+140^{\circ}\text{F}$). <i>Actual performance is typically much better than the rated values.</i>
Rated Temperature Reading Resolution	Less than 0.1°C for -30°C to $+60^{\circ}\text{C}$.
Sensor Reaction Time	Typically less than 7 minutes (T90) in moving air (1m/s).
Recording Capacity	1st activation of each alarm for each day including trigger time and duration of each excursion.
Sampling Interval	1-15 minutes, factory set to 6 minute interval for profile 0006 (i.e. 0.1hour).
Logging Start Options	Push button start or specific date.
Recording Indication	Alarms are displayed on a custom LCD.
Environmental	IP64.
Power Source	CR2032 3V LiMnO ₂ Battery (Fixed).
Battery Life	Minimum storage life of 5 years before 'start'. Monitoring period: 40 days. Minimum accessibility (display) period of 6 months after 'stopped'.
Real Time Clock	Built-in real time clock. Typical accuracy $\pm 25\text{ppm}$ @ 25°C (equivalent to 2.5 seconds/day). Rated temperature coefficient is $-0.034 \pm 0.006\text{ppm}/^{\circ}\text{C}$ (i.e typically ± 0.00294 seconds/day/ $^{\circ}\text{C}$).
Size	73mm(H) x 54.5mm(W) x 8.6mm(T).
Weight	30g.
Case Material	Polycarbonate.



WessexPower
Solutions for High-tech Instrumentation
www.wessexpower.co.uk

LSTechnology
E-commerce Instrumentation
www.loggershop.co.uk

Telephone +44(0)1929 459 459 Email sales@WPLS.co.uk